


Mounted Mould Board Plough



High quality blade & bar point



Drawbar adjustment



Rugged frame



BENEFITS

- It can handle the tougher ploughing job with outstanding performance like penetration & inversion.
- It is designed to work in all types of soil, for soil breaking, soil raising and soil turning.
- It can be used in stony & rooted soils too.

FEATURES

- The under-frame and unit-to-unit clearance are adequate to cope with trashy conditions.
- Adding an extra furrow or repositioning units to allow for extra clearance is quick and easy.
- The plough has special wear-resistant steel blade with bar points for toughest ploughing jobs.
- Bar point having longer life, as they can be extended till the last possible length.

SPECIFICATIONS

DESCRIPTION	FKMBP36-2	FKMBP36-3	FKMBP36-4
FURROW	2 FURROW	3 FURROW	4 FURROW
FRAME	80x80x7 mm Box	80x80x7 mm Box	80x80x7 mm Box
DRAWBAR ROD	2" Solid Rod	2" Solid Rod	2" Solid Rod
TYNE	25 & 36 mm Profile Cut Single Piece	36 mm Profile Cut Single Piece	36 mm Profile Cut Single Piece
LENGTH	51"	74"	97"
HEIGHT	42"	42"	42"
BLADE	10 mm	10 mm	10 mm
MOULD BOARD	8 mm	8 mm	8 mm
BAR POINT	40x25 mm Bar (Forged)	40x25 mm Bar (Forged)	40x25 mm Bar (Forged)
3 POINT LINKAGE LEVER & CONNECTING ROD	65x16 mm Flat & 32 mm Square	65x16 mm Flat & 32 mm Square	65x16 mm Flat & 32 mm Square
WIDTH OF CUT	2 Feet	3 Feet	4 Feet
DEPTH OF CUT	14"	14"	14"
WEIGHT	467/518 Lbs (approx)	783 Lbs (approx)	1003 Lbs (approx)
POWER REQUIRED (HP)	30-40	55-60	80-90