


Pendular mounting enables the cutter to follow contour of the ditch when control cylinder is in the float position



Thrifty Tool Arm specifically made to meet all your needs.





Tool Arm Raised to Transport Folding position



Tool Arm in Transport Position
(weight is close to centerline of tractor)

Transport arm in the collapsed position to reduce stress to the arm and also to stabilize the weight.

Main lift cylinder is equipped with a pilot operated check valve to prevent the arm from drifting in the working position and also to retain arm safely in the transport position.

Breakaway Linkage
to protect equipment from damage if outer corner or cutter contacts an obstruction.



Tool Arm Stand
when tractor is unhitched.



Thrifty Tool Arm

- Weight 900 lbs.
- Capacity Max. 800 lbs
- Offsets Machine 84"
- Tractor size requirement 5' cutter min 60 hp
- Tractor size requirement 6' cutter min 80 hp
- Cuts @ 55 with cylinder extended
- Cuts @ 90 with cylinder retracted
- Requires 2 remote outlets
- Cat. 1 & 2
- Pilot operated check valve to prevent drift in working position



PTO holder
used in transport position.



Counterweight Bracket
(extended) for suitcase weights add up to 500 lbs of counter weight.

AUTHORIZED DEALER

3950 Steffler Rd.
Elmira, Ontario
Canada N3B 2Z3
Tel: 519-664-2752
Fax: 519-664-3695

PRINTED IN CANADA

