


GASPARDO


MASCHIO GASPARDO S.p.A.

REGOLAZIONE DISTANZE DI SEMINA
SEEDING DISTANCE ADJUSTMENT
AUSSAATLÄNGSABSTAND
DISTANCE LONGITUDINALE D'ENSEMENCEMENT
DISTANCIA LONGITUDINAL DE SIEMBRA
ТАБЛИЦА ПРОДОЛЬНЫХ РАССТОЯНИЙ ПОСЕВА




Cambio
Gearbox
Getriebe
Boîté vit.
Cambio
Смена

16 17 18 19 20 21 **B**



A 15 21



Ruota
Wheel
Rad
Roue
Rueda
Колесо
5.00-15

Cod. G19708000

Ruota Wheel C - D	Cambio Gearbox A - B	120	90	75	45	24
		inch	inch	inch	inch	inch
10	21 - 16	0,25	0,33	0,40	0,66	1,24
	21 - 17	0,26	0,35	0,42	0,70	1,31
	21 - 18	0,28	0,37	0,45	0,74	1,39
	21 - 19	0,29	0,39	0,47	0,78	1,47
	21 - 20	0,31	0,41	0,49	0,82	1,55
	21 - 21	0,32	0,43	0,52	0,87	1,62
20	15 - 16	0,35	0,46	0,55	0,92	1,73
	15 - 17	0,37	0,49	0,59	0,98	1,84
	15 - 18	0,39	0,52	0,62	1,04	1,95
	15 - 19	0,41	0,55	0,66	1,10	2,06
	15 - 20	0,43	0,58	0,69	1,15	2,17
	15 - 21	0,45	0,61	0,73	1,21	2,27

Ruota Wheel C - D	Cambio Gearbox A - B	120	90	75	45	24
		inch	inch	inch	inch	inch
15	21 - 16	0,49	0,66	0,79	1,32	2,47
	21 - 17	0,53	0,70	0,84	1,40	2,63
	21 - 18	0,56	0,74	0,89	1,48	2,78
	21 - 19	0,59	0,78	0,94	1,57	2,94
	21 - 20	0,62	0,82	0,99	1,65	3,09
	21 - 21	0,65	0,87	1,04	1,73	3,25
	15 - 16	0,69	0,92	1,11	1,85	3,46
	15 - 17	0,74	0,98	1,18	1,96	3,68
	15 - 18	0,78	1,04	1,25	2,08	3,90
	15 - 19	0,82	1,10	1,32	2,19	4,11
	15 - 20	0,87	1,15	1,39	2,31	4,33
	15 - 21	0,91	1,21	1,46	2,43	4,55

Ruota Wheel C - D	Cambio Gearbox A - B	120	90	75	45	24
		inch	inch	inch	inch	inch
20	21 - 16	0,99	1,32	1,58	2,64	4,95
	21 - 17	1,05	1,40	1,68	2,80	5,26
	21 - 18	1,11	1,48	1,78	2,97	5,57
	21 - 19	1,18	1,57	1,88	3,13	5,88
	21 - 20	1,24	1,65	1,98	3,30	6,19
	21 - 21	1,30	1,73	2,08	3,46	6,50
	15 - 16	1,39	1,85	2,22	3,70	6,93
	15 - 17	1,47	1,96	2,36	3,93	7,36
	15 - 18	1,56	2,08	2,49	4,16	7,80
	15 - 19	1,65	2,19	2,63	4,39	8,23
	15 - 20	1,73	2,31	2,77	4,62	8,66
	15 - 21	1,82	2,43	2,91	4,85	9,09

The above indicated seed spacing are theoretical since they are affected by different working conditions. The Manufacture will not be held liable for any inconsistencies between the values of the table and the actual values found.



Lubrificare con: **BLASIA 220**
Vedi libretto istruzioni