




pag 148-151



PRE-PRUNING MACHINE CPL TOWER 1 PLUS WITH HOSES TO THE TRACTOR

Standard machine:

T1 PLUS FRAME	SAFETY	ON THE TRACTOR
<ul style="list-style-type: none"> - Hydraulic lifting cm 70 - Hydraulic tilting vertical frame +/-20° - Hydraulic side shift cm 60 - Manual tilting of the working head +/-15° - Electro-hydraulic opening with push button and locking - Quick connection PLUS 	<ul style="list-style-type: none"> - Maximum pressure valve and flow divider motor - Maximum pressure valve for opening - Hydraulic stand for storage 	<ul style="list-style-type: none"> - N.3 double-acting hydraulic distributors - N.1 single-acting hydraulic distributor - N.1 pressure free return - 25-35 Liter/min

CODE	MODEL	DISCS N.	B cm min	B cm MAX	A cm
6CPLT104NA	CPL T1 A 4+4	4+4	85	142	30
6CPLT106NA	CPL T1 A 6+6	6+6	85	142	50
6CPLT108NA	CPL T1 A 8+8	8+8	85	142	70
6CPLT110NA	CPL T1 A 10+10	10+10	85	142	90
6CPLT106GA	CPL T1 A 6+6 G (compact)	6+6	85	142	35
6CPLT108GA	CPL T1 A 8+8 G (compact)	8+8	85	142	49
6CPLT110GA	CPL T1 A 10+10 G (compact)	10+10	85	142	63

CODE	ACCESSORIES
+I	Price increase for hydraulic distributor 4+1 with levers for tractors without cabin
+E	Price increase for electro-hydraulic controls with joystick 4+1 for tractors with cabin
+F	Price increase for electro-hydraulic controls with joystick 7+1 for tractors with cabin
4525001	Hydraulic tilting head +/- 15° (+1 movement)
45180	Price increase for 100cm lifting frame (recommended for model 6CPLT1110A)
39989	Price increase for saw discs instead of the lowest discs
39988	Kit additional saw discs added under the lowest discs (e.g. the 8+8 head becomes 9+9)
38890	Side dry cutting bars kit 65cm for with joints

N.B. The standard machine is equipped with 3 hydraulic movements, it is possible to add 1 single hydraulic movement without replacing the hydraulic distributor or joystick 4+1.

NB: All models are equipped as standard with 1.5m-long hydraulic hoses from the coupling plate. For longer hoses a price increase of € 15,00 per meter per hose will be added.

